

# ECOTECH TAURUS SERIES

ECO-SOLVENT PRINTERS

UP TO  
**2880**  
dpi

UP TO  
**366**  
sq.ft./h



Speed, quality and production savings in eco-solvent printing

**PARADIGM**  
IMAGING GROUP

Paradigm Imaging Group - [www.paradigmimaging.com](http://www.paradigmimaging.com)

1080 Batavia Street Suite M, Orange, CA 92867 | 888.221.SCAN(7226)

The ECOTECH TAURUS SERIES Eco-Solvent Printers provide both cutting-edge technology and lower production costs in easy to operate models. **The 126" wide ECOTECH TAURUS 320 features 2 Epson DX5 printheads with resolutions as high as 2,880 dpi to achieve picture perfect quality.**

With support for both local and remote printing, high speed data transfers up to 480Mb/sec efficiently process the most demanding graphic applications. Reliable production is guaranteed by the double column vertical balance guide rail, automatic intelligent print head cleaning and moistening, as well as by the enhanced feathering print mode.

The high capacity bulk ink system lowers your cost by utilizing 1 liter CMYK inks with 500 ml reserve cartridges. The front heaters and drying fans quickly dry jobs for continuous production when utilizing the printer's automatic take-up system.



Heater temperature controllers

Ink cartridges with 1 liter capacity per color

**EPSON**  
EXCEED YOUR VISION

Up to 2 Epson DX5 Printhead  
1440 nozzles



**1 Year Limited Warranty**

**ECOTECH TAURUS 180**

**ECOTECH TAURUS 320**

Printhead	1440 nozzles · variable dots · 7 / 14 / 21 picoliters		
Number of Printheads	1		
Resolution	Up to 1440 DPI		<b>Up to 2880 DPI</b>
Ink	Eco-Solvent   4 colors (CMYK)   1 liter per color Bulk System		
Maximum printing width	70" (1,800 mm)		<b>126" (3,200 mm)</b>
Auto feeding/take-up system	Roll or sheet		
Media	Banner, mesh, vinyl, perforated vinyl, canvas, textile, polyester fabric, etc		
Print Speed	Production	4 passes	161 sq.ft./h (15 m <sup>2</sup> /h)
	Quality	6 passes	129 sq.ft./h (12 m <sup>2</sup> /h)
	High Quality	8 passes	86 sq.ft./h (8 m <sup>2</sup> /h)
			<b>366 sq.ft./h (34 m<sup>2</sup>/h)</b> <b>269 sq.ft./h (25 m<sup>2</sup>/h)</b> <b>194 sq.ft./h (18 m<sup>2</sup>/h)</b>
Cleaning system	Auto cleaning		
Heating and drying system	Pre and front heaters and drying fans		
RIP Software	MainTop RIP. FlexiPrint 12 Optional		
Interface	Network interface RJ45		
Voltage	AC 220 V · 50 / 60 Hz		
Package dimensions	111" x 28" x 28"		<b>191" x 28" x 35"</b>
Equipment dimensions	109" x 39" x 50"		<b>179" x 39" x 50"</b>
Equipment weight	Net: 330 lb (150 kg) Gross: 441 lb (200 kg)		<b>Net: 1,366 lb (620 kg) Gross: 1,653 lb (750 kg)</b>